QuestVapco

THUNDER

Organic Foaming
Engine Degreaser

600005824

Organic Foaming Engine Degreaser

Organico Espuma Desengrasante de Máquinas

Dense Clinging Foam – Will Not Run

Spray On – Wash Off

Dissolves Oil, Tar, Grease, Dirt, Stains, Road Oil

Cleans Gasoline & Diesel Engines, Metal, Concrete, Brick, Stone

CAUTION / PRECAUCIÓN

EYE AND SKIN IRRITANT. CONTENTS UNDER PRESSURE
KEEP OUT OF REACH OF CHILDREN
SEE OTHER CAUTIONS ON BACK PANEL

OJO Y PIEL IRRITANTE. CONTENIDO BAJO PRESIÓN
NO SE DEJE AL ALCANCE DE LOS NIÑOS
VEA PRECAUCIONES ADICIONALES EN EL PANEL TRASERO

NET WT. 17 OZ. (482 g)

QuestVapco Corporation
Brenham, TX • St. Louis, MO

THUNDER works quickly to emulsify tar, asphalt, grease and oil. This product is safe and easy to use. Spray on and wash off with water. Dense foam allows product to cling to vertical surface allowing for longer contact time. Cleans engines enabling them to run cooler, look better and last longer. Biodegradable and VOC compliant in all 50 states.

GREAT FOR THESE APPLICATIONS:
Engines • Appliances • Road Equipment
Exhaust Vents • Motors • Vehicles • Rims
Tools • Refrigeration Coils • Machinery
Industrial Equipment • Concrete • Etc.

DIRECTIONS FOR USE: When using on painted surfaces, test a small area to be sure paint is not affected. Hold can eight to ten inches from the surface to be sprayed. Apply a thorough coating, being sure to cover all grease, oil or tar.

FOR ENGINES: Cover carburetor intake and distributor with plastic or aluminum foil before using to avoid water contamination. Allow product to set for fifteen minutes to allow complete penetration and emulsification. Hose off with strong stream of water. Remove plastic or aluminum foil and run engine for fifteen minutes to insure complete drying.

OTHER SURFACES: To remove oil, grease, tar and asphalt from other surfaces, apply to surface covering area to be cleaned completely. Allow product to work for ten to fifteen minutes. Wash off with a strong stream of water. Heavily soiled areas may require scrubbing or a second application.

MODO DE EMPLEO: Cuando se use en superficies pintadas, pruebe en un área pequeña para asegurar que la pintura no sea afectada. Sostenga el bote de 8 a 10 pulgadas del área que se va a rociar. Aplique una capa asegurándose de cubrir toda la grasa, aceite y alquitrán.

PARA MOTORES: Cubra la toma del carburador y el distribuidor con plástico o papel aluminio para evitar contaminación con agua. Permita que el producto actúen por 15 minutos para que ocurra una completa penetración y emulsificación. Limpie con manguera. Remueva el plástico o papel aluminio y encienda el motor por 15 minutos para que se seque bien.

OTRAS SUPERFICIES: Para remover aceite, grasa, alquitrán y asfalto de otras superficies, aplique sobre la superficie cubriendo el área que se va a limpiar. Permita que el producto trabaje por 10 o 15 minutos. Lave con un fuerte chorro de agua. Áreas muy sucias pueden ser talladas o un segunda aplicación.

CAUTION: Use only in a well ventilated area. Keep away from heat, sparks or open flame. Allow areas where product has been sprayed to ventilate thoroughly before using or energizing equipment. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. Contents under pressure. Avoid contact with eyes and skin.
NOTE: This product produces vapors that are flammable when concentrated or confined.

PRECAUCIÓN: Use solamente en áreas bien ventiladas. Mantenga lejos del calor, chispas o llama abierta. Permita que el área adonde el producto a sido rociado que se ventile antes de usar. No perfore o incinere el envase. No exponga al calor o almacene en temperaturas encima de 120°F. Contenido bajo la presión. Evita contacto con ojos y piel.
NOTA: Este producto produce vapores que son inflamable cuando son concentrado o confinados.

CONTAINS (CAS#): Water (7732-18-5), Propane/n-Butane (68476-86-8), Diethylene Glycol Monobutyl Ether (111-34-5), Isoparaffinic Hydrocarbon (64742-47-8), Nonionic Surfactant (127087-87-0).

HEALTH	1
FLAMMABILITY	1
REACTIVITY	0
PERSONAL	B

8 31788 00215 9

ITEM 824000001

Made in USA

SPECIMEN